

parchet laminat
folie poliester/ polistiren
placa groasa OSB 22mm
structura plansele - grinzi lemn rasinoase 12x18
vata minerala 15 cm grosime- rol fonoizolator
structura metalica si travan fals gips carton

+10.61^s

Inclinare = 40-10 ‰

acces
propus

2.05

2.25

1.20

0.7

+6.00

-6.00

+5.20

+3.90

+3.00

+2.70

±0.00

±0.00

-2.30

ETAJ 2

ETAJ 1


PARTER

SUBSOL
LOCAL

VEDERE V1- V1- ZONA POSTERIOARA FATADA CURTE
CU SECTIUNE TRANSVERSALA V1-V1- PROPUIS

COLORISTA FATADE
Tencuiala decorativa – Alb-gri(alt usor murdar ,
Ancadramele - Gri deschis
Soclu - Gri inchis-similpiatra la imprejmuire
Tamplarie Aluminiu – culoare albastru marin
Invelitoare Profilata- Gri -similar RAL 7040
Jgheaburi, Burlane - culoare gri RAL 7040



<div></div>	Categoriza de importaanta C - normala			<div>Beneficiar CRISTESCU ANDREI CRISTESCU OANA</div>	<div>TEMA PROIECT Consolidare supraealare, rezulta constructie S+ P+2E, refaceere imprejmuire, amenajare incinta BUCURESTI str. Gligore Raducanu nr. 2 sector 1 denumire planşa</div>	<div>Faza proiect D.T.A.C.</div>	<div>SCARA 1: 50 Proiect nr. 02A-5-2020</div>
	Clasa de importaanta III						
	Grad de rezistenta la foc - II						
	Risc mic de incendiu						
	In executie OS, se organizeaza in incinta						
Se vor respecta Norme Protectia Muncii Legea 319/2006 si P118/90							